

General Catalog


Unlocking the full potential of your machines



You might as well try to move a mountain

EROWA'S UPC (Universal Power Chuck) breaks through the conventional limits of precision, stability and workpiece size. Now, 500 x 500 x 500 mm have ceased to be a problem. And the 2-µm precision will not be impaired at all.

A decisive factor for ITS users: the central ITS chuck guarantees seamless integration into the existing system.



Applications








Manual / Loading facility / Robot

Function



UPC open



UPC closed

The functional elements have been designed with every conceivable simplicity. This makes for a favorable price. The few movable parts guarantee high functional safety.

The lock crea-tes a retaining power of 50,000 N. The big distance between the supports creates an extreme degree of platform stability.

Precentering is done by means of the chucking spigots. Precise positioning is then achieved by four stable centering segments in the pallet and chuck. Release and cleaning are achieved by means of compressed air.

Technical data - UPC			
	UPC	UPC P «Production»	
Pallet size	320 x 320 mm	320 x 320 mm	
Chuck dimensions	280 x 280 mm	320 x 300 mm	
System height			
(chuck and pallet)	105 mm	105 mm	
Recommended			
workpiece sizes	500 x 500 x 350 mm	500 x 500 x 500 mm	
Repeatability	0.002 mm	0.002 mm	
Indexation, pallet	4 x 90° 4 x 90°		
Activation	clamped without pressure	9	
Air pressure, dry	min. 6 bar	min. 6 bar	
Operation	manually or with automatic control unit		
Process monitoring	pneumatically, evaluatior	pneumatically, evaluation electro-pneumatically	
Clamping power	32,000 N	50,000 N	



EROWA UPC in operation

Universal, powerful, micronaccurate


The UPC tooling system is suitable for flexible use. Whether big electrodes on the quill of EDM centers or big workpieces in milling machines: the UPC has been designed to cope with them, and it does.


With a repeatability of 2 μm , the UPC does not leave any wishes unfulfilled with regard to precision, either.


RELIABLE

Resistant to dirt.

Robust - developed for continuous operation.








Customized solutions including. We'll be happy to advise you!



Low construction height leaves much room for workpieces.



Suitable PreSet stations are available for setting up and presetting - manual or CNC.




Practical! EDMing on the UPC magnet pallet.



On a clamping surface of up to 500 x 500mm, even large workpieces or fixtures can be attached to the UPC pallet without any problems.



Powerful in heavy machining.



2 in 1: UPC adapter pallet with EROWA PowerChuck P.



Flexible and modular. EROWA self-centering vise 148 on UPC pallet.



UPC Pallet Alu DG – light and handy.



Short set-up times with flexible clamping elements: EROWA ClampSet vises on UPC grid pallet.



The UPC on the machine table constitutes the interface with the workpiece carrier. Resetting takes next to no time, and production can resume.






From a manual handling unit to a complex robot system - EROWA provides the handling solution that you desire.

Palletizing System

The components



To make it easier for you to find your way about the fields of application for EROWA products, we use the following symbols in all our documents:



1. Manual operation



2. Operate with compressed air jet



3. Operate with manual valve



4. Operate with manual control unit



5. Operate with electropneumatic control unit



6. With central flushing clearance



7. Suited for submerged operation



8. Corrosion-resistant material



9. Suited for automatic operation



10. Handling with EROWA Robot gripper S



11. Handling with EROWA Combi gripper



12. Handling with EROWA Robot gripper 72



13. Handling with EROWA Robot gripper 115



14. Handling with EROWA Robot gripper 148



15. Handling with EROWA gripper RN PC 210



16. Handling with EROWA RCS gripper



UPC chucks 58 UPC pallets 59 UPC auxiliary equipment 60



For chip-removing processes



For EDM sinking



For WEDM

EROWA UPC Chucks

Technical data	UPC	UPC P «Production»	ITS Chuck 100P	PowerChuck
Repeatability	0.002 mm	0.002 mm	0.002 mm	0.002 mm
Indexing, pallet position-oriented	4 x 90°	4 x 90°	4 x 90°	4 x 90°
Chuck clamping power	32,000 N	50,000 N	6000 N	10 000 N
Generated by	spring power	spring power	spring power	spring power
Chuck opens, air pressure dry	min. 6 bar	min. 6 bar	min. 6 bar	min. 6 bar

ER-074524 UPC chuck




Version UPC, prepared to accommodate an ITS chuck 100P.

Connections On the side.

Application On milling, grinding, drilling and EDM sinking centers.

In production lines.



ER-070649 UPC chuck with ITS Chuck 100 P






Version UPC with ITS chuck 100P fitted and aligned.

UPC system automatable.

Connections On the side.

Application On milling, grinding, drilling and EDM sinking centers.

In production lines.



ER-016841 UPC P chuck






Version Chuck for high machining forces during chip removal.

Connections Through the base and on the side.

Application On milling, grinding, drilling and EDM centers.

In production lines.

Option UPC Sealing-Set ER-016650.



ER-030581 UPC P / PowerChuck P kit automatic





Version UPC P with air dock for the automatic operation of Power-

Chuck P.

Content 1 x ER-028784, UPC P with air duct and UPC seal kit,


1 x ER-030580, PowerChuck P on UPC pallet with air duct,

1 x Pneumatic tube.

Requirements *At least 4 air ducts available on the machine table.

*Air ducts for the PowerChuck P are only possible laterally.

If required, an adapter plate can be used.



Pallets








Version Aluminum, with centering segments and chucking spigots


fitted. Hard Z-support.

Application To clamp workpieces and gauges. Holes to be drilled as required. Please note



UPC pallet Alu R50 320 x 320 x 40 ER-018570 eloxed

UPC pallet Alu R50 320 x 320 x 40 ER-016003








Aluminum with 50mm grid. Centering segments and Version

chucking spigots fitted. Hard Z-support.

Application Basis for gauges and workpieces. Info Pattern borehole ø 12F7, M12 thread.

Please note The elox version is not suited for use in EDM machines.



UPC pallet Alu diecast ER-022898

ER-022896 **UPC** pallet Alu diecast S







Handles integrated. Steel Z-support.

Application To clamp workpieces and gauges.


ER-022898: centering segment integrated in aluminum Please note

(repeatability: 0.005 mm).

ER-022896: with steel centering segment fitted

(repeatability:0.002 mm).

Order separately: ER-032503, M10 insert nut. Accessories





ER-039444 **UPC** magnet plate Neomicro








Version **Application**

Version

Magnet plate assembled as a UPC pallet 320 x 320 x 58 mm. To clamp workpieces for surface and profile grinding, EDM

sinking, and high speed milling.



Auxiliary equipment

ER-024932 **UPC** centering segments and chucking spigots, for mounting from above






Four segments and chucking spigots for UPC, Version

including bolts.

Application To produce special UPC pallets.

With bolts through the pallet from above. Mounting Note Easy to assemble on the UPC chuck.



ER-024562 **UPC** centering segments and spigots

to mount from lower side






Version Four segments and chucking spigots for UPC,

including bolts.

Application To produce special UPC pallets.

With bolts through the pallet from below. Mounting Easy to assemble on the PreSet Basic UPC Note

presetting station.



ER-048377 **UPC** alignment pallet






Application To align angular position and to determine the center of

UPC chucks.

System parallelism 0.005 mm. Please note

Borehole concentricity 0.005 mm.



ER-029453 PowerChuck P on UPC pallet






Version Adapter pallet UPC - PowerChuck P.

Connections Laterally on pallet.


Application On machining centers. Operate with air-jet or fixed

Manual change into UPC. Possible automatic change Note


into PowerChuck P.




ER-008988	Manual control unit
Version	Manual valve to control all the functions of ITS, ITS Compact CombiChuck, PowerChuck P and UPC: opening/reclamping/cleaning.
Application	Operation of chucks on machines.



ER-039466	Additional valve double
Version	For mounting to the manual control units ER-008988 and ER-025893, incl. set of hoses.
Application	Operating of two separate chucks with one single control unit.




ER-016531	UPC air jet connection
Version	Valve for the manual operation of UPC ER-016092, ER-016093, ER-074527 and ER-070649 with an air jet.
Application	To be fitted on UPC cover.




ER-018168	UPC P air jet connection
Version	Valve for the manual operation of UPC P ER-016841 with an air jet.
Application	To be fitted on UPC P cover.

ER-012444

Version Application










Auxiliary equipment

ER-012441 Cover set for UPC / ITS



Version Aluminum with inserts for 51, ø 72, ø 115, ø 148 pallets

and for electrode holders for UPC ER-016092.




ER-018247 Cover UPC pallet ø 148



Version Aluminum. Cover for UPC ER-016092.

Application Protects UPC system when ø 148 mm pallets are used in

the ITS central chuck.



ER-016650 UPC sealing kit




Version Rubber seal and frame.

Application To seal the UPC P against chips.

Mounting With supplied bolts.

Please note Fits UPC No. ER-016092/ER-016093/ER-016841.



ER-018718 UPC clamping bracket


4 pieces



Version High tension steel, mounting accessories not included.

Application To mount UPC chucks to machine tables.

Please note Fits UPC chuck No. ER-016092/ER-016093/ ER-016841.



ER-015661 Handles for UPC pallets / FrameSet 2 pieces



Version Aluminum die-casting, set of 2 units. Application Safe handles for UPC pallets.

Mounting With the enclosed bolts to the prepared threads.



50 pieces



Version Set of 50, including square wrench.

Application Plastic bolts to seal grid boreholes that are not in use.

Suitable for ER-018570 and ER-016003.



ER-022646 Plug ø 10.6 x 20

50 pieces



Version Set of 50.

Application Plastic plug to seal grid boreholes that are not in use.

Suitable for ER-022898 and ER-022896.




ER-036347 **GripperLink RCS / EWIS™ Rapid**



Coupling for UPC pallets, mounting accessories included. Version Suited for UPC pallets to be used on EROWA handling Application

devices with the «RCS coupling system».



ER-035294 **EWIS™** Rapid chip with chip holder RCS

with chip ø 12,4 x 2 mm



Version Holder with built-in datacarrier.

EWIS chip: read only.

To build into RCS coupling, PalletSet W holder and Application

Basic WEDM holder.





